

Beagle™

USB 480

Protocol Analyzer

Key Features

Real-Time Non-Intrusive Monitoring

- High-/Full-/Low-Speed USB 2.0 (up to 480 Mbps)
- Digital inputs and outputs to synchronize with oscilloscopes or logic analyzers
- 16.7 ns resolution

Real-Time USB Class-Level Decoding

- HID, Audio, Video, Still Image, Printer
- Mass Storage, Hub
- Network, Mobile, CDC

Data Center™ Software

- Real-time display, search, and filtering of captured data
- Descriptor decoding
- Automatic bus speed detection
- Capture traces to >25 GB
- Cross-platform support for Windows, Linux, macOS

Beagle API

- Create custom software applications
- Example files included

USB Bus-Powered

- Portable
- No extra power adapters needed

Quality

- CE, REACH, RoHS
- Manufacturing: ISO 9001, ISO 13485, AS9100C, ITAR
- One year warranty

Beagle USB 480は2007年発売以来ハードウェアの変更なしで売れ続けているUSB2.0プロトコルアナライザ。USB機器開発、検査、トラブル対応、セキュリティ用途などで大量にご利用いただいています。バス状態をプロトコルデコードしてキャプチャしながら表示、フィルタ、サーチをライブで行えるアナライザGUIアプリのData Centerと、カスタムアプリが作成できるAPIが付属します。お問い合わせは立野電脳(株) sales@dsp-tdi.com



An ever-wider array of devices and the increasing pressure to minimize costs means that you need to get the most out of your embedded systems interface tools - and the Beagle USB 480 Protocol Analyzer is expressly designed to enable your competitive edge.

The Beagle USB 480 Protocol Analyzer is the ideal tool for debugging and monitoring traffic on your high-, full-, or low-speed USB based applications. The Beagle analyzer provides a high performance and powerful monitoring solution in a small, portable package. It provides fast, interactive, real-time visibility into the protocol layer of your embedded system.

Enhanced Visibility

- Interactive debugging: make a change and see the result in real-time
- Real-time filter displays user-defined views
- Longer recording buffer than a scope (data streamed to PC's memory)
- Collaborate easily by sharing saved captures with colleagues with Data Center software

Class-Level and Descriptor Parsing

- Class-level decoding translates raw data into human-readable text in real-time
- Descriptors parsed in real-time during enumeration

Enumeration Debugging

The Beagle USB 480 analyzer is capable of analyzing all USB traffic that is passed through its ports, including the enumeration process. Many USB communication errors occur during this initial "handshake" between host and device. The analyzer is able to capture and display low-level bus events (K/J chirp pairs), dataless transactions (suspend/resume events), and parse all the descriptors, enabling USB developers to quickly and easily identify problems in their application.



立野電脳 EXT営業部
E-mail : sales@dsp-tdi.com
〒198-0063 東京都青梅市梅郷5-955 TEL.0428-77-7000

URL <https://www.dsp-tdi.com/>

Beagle™ USB 480 Protocol Analyzer

Applications

Audio
Bridges
Cameras

HID
Hubs
Mass Storage

Mobile Broadband
Mobile Phones
Music Players

Tablets
Video



Specifications

Software

The Data Center™ Software is a bus monitoring software application that displays captured USB, I2C, SPI, and CAN bus data in true real-time through the Beagle™ line of hardware protocol analyzers and the Komodo™ line of CAN interfaces.

Data Center Software Features


- LiveDisplay™ technology allows for real-time interactive display and analysis of high-, full- and low-speed USB (up to 480 Mbps)
- Automatic class-level decoding and descriptor parsing
- LiveFilter™ and LiveSearch™ tools allow for real-time interactive filtering and searching
- Collaborate easily by sharing capture files
- Export saved capture files to CSV format

Beagle API

- Create custom applications using the flexible, powerful, and well-documented Beagle API
- 32- and 64-bit support for C/C++/C#, Python, .NET, VB.Net, VB 6

Operating Systems Supported (32-bit and 64-bit)

- Windows: 7, 10, 11, and later
- Linux: Red Hat, SuSE, Ubuntu, Fedora
- macOS: 13 and later



Data Center

Hardware

USB Monitoring:

High Speed, 480 Mbps
Full Speed, 12 Mbps
Low Speed, 1.5 Mbps

Target Device Port:

USB 2.0 Type A receptacle

Target Host Port:

USB 2.0 Type B receptacle

Analysis Port (connects to PC):

USB 2.0 Type B receptacle
Analyzer is bus-powered

Digital I/O Port:

Mini DIN 9 connector
4 inputs, 4 outputs, 1 ground
Digital inputs are rated for 3.3 V and max 30 MHz
Digital outputs are rated for 3.3 V and 10 mA

Dimensions (W x D x L)

70 mm x 26 mm x 114 mm (2.76 in x 1.02 in x 4.49 in) **Weight**
97.5 g (0.21 lbs)

Operating Temperature

10 to 35 °C (50 to 95 °F)



EXT営業部

E-mail : sales@dsp-tdi.com

〒198-0063 東京都青梅市梅郷5-955 TEL.0428-77-7000

URL <https://www.dsp-tdi.com/>

Ordering information

"Beagle USB 480 TP320510" でお問い合わせください

Part Number TP320510

Country of Origin USA

HTS 9030890100

ECCN EAR99



+1 (408) 850-6501 | sales@totalphase.com | www.totalphase.com

©2025 Total Phase, Inc. All rights reserved.

R20250327